

BRUSHING MACHINE

LA-HO

LAH01.03.1809.GB



The LA-HO small-scale brushing machine is designed for batch or continuous processing of small volumes of seeds or grain prior to cleaning and grading processes

The LA-HO brushing machine is mainly used for brushing the surface on different seeds and grain products (e.g. bunt on wheat, saponin from quinoa, and oats for horse feed).

Dust and brushed off particles are removed by air at the bottom of the unit and the product is led out at the end of the mantle.

For more technical information see the back page.

The LA-HO brushing machine offers the below features:

- Inlet with capacity shutter and vibrator feeder.
- One-section exchangeable mantle.
- Air intake for aspiration in full length of the mantle.
- Rotating shaft with two internally adjustable brushes or steel beaters.
- Manually adjustable brushing degree.
- Inspection window at outlet end.
- Outlet with rotary valve for product from the end of the mantle.
- Connection pipe for external aspiration system.
- Control box.
- Drive motor with frequency converter.

The machine is of steel construction.

Options:

- *Vacuum cleaner with collecting bucket*
- *Autotransformer for 110 V, 60 Hz*

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions

BRUSHING MACHINE LA-H0

TECHNICAL SPECIFICATIONS:

	LA-H0
Motors V	1 x 230
Motor with frequency converter for setting the speed of the brushes/beaters kW	0.75
Motor for rotary valve W	6

DISTINGUISHING ADVANTAGES:

- Air intake with filter cloth for suction in the entire length of the mantle to secure a very clean operation
- Inspection window at the outlet end making it possible to follow the process inside
- Electrical controls for easy connection into a 230 V outlet; Autotransformer for 110 V also available
- Easy clean-down when changing from one product to another
- Low maintenance costs

